

FORM PTO-1390 (REV 10-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER P/4074-8	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO (If known, see 37 CFR 1.5) 10/089363	
INTERNATIONAL APPLICATION NO. PCT/EP00/09301		INTERNATIONAL FILING DATE 22 September 2000		PRIORITY DATE CLAIMED 24 September 1999	
TITLE OF INVENTION DEVICE FOR MEASURING PHYSICAL QUANTITIES, ESPECIALLY FOR MEASURING PRESSURE IN THE EYE					
APPLICANT(S) FOR DO/EO/US Christine KREINER et al					

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:


1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☒ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).


Items 11 to 16 below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment. **EXPRESS MAIL CERTIFICATE**
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

Print EFS Form
3 Drawing Sheets
(Figs. 1-7)
Intl. Search report
Inventors Designation Sheet
(Unsigned Declaration)

I hereby certify that this correspondence is being
deposited with the United States Postal Service as Express
Mail Post Office to Addresses (mail label
EL924372465US in an envelope addressed to:
**U.S. Patent and Trademark Office, P.O.
Box 2327, Arlington, VA 22202 on
March 25, 2002**

Dorothy Jenkins
Name of Person Mailing Correspondence

Signature
March 25, 2002
Date of Signature

U.S. APPLICATION NO. 107089363 INTERNATIONAL APPLICATION NO. PCT/EP00/09301		ATTORNEY'S DOCKET NUMBER P/4074-8	
17. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1,040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO 890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO 740.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) 710.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =		CALCULATIONS PTO USE ONLY	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).		\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	18 - 20 =	0	X \$18.00
Independent claims	1 - 3 =	0	X \$4.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$20.00
TOTAL OF ABOVE CALCULATIONS =		\$ 890.00	
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.		\$ 445.00	
SUBTOTAL =		\$ 445.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).		\$	
TOTAL NATIONAL FEE =		\$ 445.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property		\$	
TOTAL FEES ENCLOSED =		\$ 445.00	
		Amount to be refunded:	\$
		charged:	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$ <u>445.00</u> to cover the above fees is enclosed. Check No. 8861			
b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.			
c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>15-0700</u> . A duplicate copy of this sheet is enclosed.			
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.			
SEND ALL CORRESPONDENCE TO: OSTROLENK, FABER, GERB & SOFFEN, LLP 1180 Avenue of the Americas New York, NY 10036-8403 Tel: (212) 382 0700		 SIGNATURE: Robert C. Faber NAME <u>24,322</u> REGISTRATION NUMBER	

P/4074-8

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

Christine KREINER et al

Date: March 25, 2002

Serial No.:

Group Art Unit:

Filed:

Examiner:

For: DEVICE FOR MEASURING PHYSICAL QUANTITIES, ESPECIALLY FOR
MEASURING PRESSURE IN THE EYE

U.S. Patent and Trademark Office
P.O. Box 2327
Arlington, VA 22202

Attn: Box PCT (US/DO/EO)

AMENDMENT/SUBMISSION

Prior to examination, please amend the application as follows.

FEE CALCULATION

Any additional fee required has been calculated as follows:

 X If checked, "Small Entity" status is claimed.

	NO. CLAIMS AFTER AMENDMENT		HIGHEST NO. PREVIOUSLY PAID FOR		EXTRA PRESENT		RATE	ADDIT. FEE
TOTAL	18	MINUS	20	* =	0	X	(\$9 SE or \$18)	\$
INDEP.	1	MINUS	3	** =	0	X	(\$42 SE or \$84)	\$
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM						X	(\$140 SE or \$280)	\$
								TOTAL \$ -----

* not less than 20 ** not less than 3

If any additional payment is required, a check which includes the calculated fee of \$ _____
(OFGS Check No. _____) is attached.

In the event the actual fee is greater than the payment submitted or is inadvertently not enclosed or if any additional fee during the prosecution of this application is not paid, the Patent Office is authorized to charge the underpayment to Deposit Account No. 15-0700.

1. *Chrysomelidae* (10 species)
 2. *Curculionidae* (10 species)
 3. *Chrysomelidae* (10 species)
 4. *Curculionidae* (10 species)
 5. *Chrysomelidae* (10 species)
 6. *Curculionidae* (10 species)
 7. *Chrysomelidae* (10 species)
 8. *Curculionidae* (10 species)
 9. *Chrysomelidae* (10 species)
 10. *Curculionidae* (10 species)

)

X If checked, amendment(s) to the specification and/or claims are submitted herewith.

1. Claims:

Please amend claims 3-8, 10-13 and 15-17 pursuant to 37 C.F.R. § 1.121(c)(i) as set forth in the “clean” version attached hereto as Appendix A. Entry is respectfully requested. A version with markings to show the changes made pursuant to 37 C.F.R. § 1.121(c)(ii) is attached hereto as Appendix B.

____ If checked, the optional complete set of “clean” claims pursuant to 37 C.F.R. § 1.121(c)(3) is attached hereto as Appendix C.

REMARKS/ARGUMENT

This Preliminary Amendment is being submitted to change the multiple dependent claims to single dependent claims in order to eliminate the improper multiple dependent claims and to reduce the government filing fee.

EXPRESS MAIL CERTIFICATE

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail to Addressee (mail label # EL924372465US) in an envelope addressed to: U.S. Patent and Trademark Office, P.O. Box 2327, Arlington, VA 22202, on March 25, 2002:

Dorothy Jenkins


Name of Person Mailing Correspondence


Signature

March 25, 2002

Date of Signature

Respectfully submitted,



Robert C. Faber

Registration No.: 24,322

OSTROLENK, FABER, GERB & SOFFEN, LLP

1180 Avenue of the Americas

New York, New York 10036-8403

Telephone: (212) 382-0700

APPENDIX A
“CLEAN” VERSION OF EACH PARAGRAPH/SECTION/CLAIM
37 C.F.R. § 1.121(b)(ii) AND (c)(i)

CLAIMS (with indication of amended or new):

(Amended) 3. The device as claimed in claim 1, characterized in that the coil windings (3) are arranged in one or more planes.

(Amended) 4. The device as claimed in claim 1, characterized in that the sensor (5) is covered completely or partially by a transmission medium transmitting the physical quantity.

(Amended) 5. The device as claimed in claim 1, characterized in that the biocompatible material with which the device is covered forms the transmission medium.

(Amended) 6. The device as claimed in claim 1, characterized in that the coil windings (3) in the area of their connection to the electronic module (4) extend in a substantially rectilinear manner.

(Amended) 7. The device as claimed in claim 1, characterized in that the coil windings (3) extend substantially in the entire implant part lying outside the field of vision of the eye.

(Amended) 8. The device as claimed in claim 1, characterized in that the sensor (5) is designed as a pressure sensor.

(Amended) 10. The device as claimed in claim 1, characterized in that the sensor (5) lies outside the field of vision of the eye in an area which does not overlap the surface of the coil windings (3).

(Amended) 11. The device as claimed in claim 1, characterized in that the sensor (5) lies inside the ring formed by the coil (1).

(Amended) 12. The device as claimed in claim 1, characterized in that the implant (6) is designed as an intraocular lens, and in that the annular support (2) in the area of the optic lens part (8) has a cutout which lies inside the coil windings (3).

(Amended) 13. The device as claimed in claim 1, characterized in that oblong holes (9) are formed in the implant material between the coil (1) and the implant part lying in the field of vision, in particular the optic lens part (8) of the intraocular lens.

(Amended) 15. The device as claimed in claim 1, characterized in that the surface or surfaces in which the coil (1) is arranged extends or extend approximately perpendicular to the optic axis (10) of the implant (6) designed as an intraocular lens.

(Amended) 16. The device as claimed in claim 1, characterized in that the coil (1) is arranged on one surface and the electronic module (4) on the other surface of the annular support (2; 16).

(Amended) 17. The device as claimed in claim 1, characterized by an annular implant body (16) made of at least partially flexible material which forms the support for the coil (1).

APPENDIX B
VERSION WITH MARKINGS TO SHOW CHANGES MADE
37 C.F.R. § 1.121(b)(iii) AND (c)(ii)

CLAIMS:

3. The device as claimed in claim 1 [or 2], characterized in that the coil windings (3) are arranged in one or more planes.

4. The device as claimed in [one of claims 1 through 3] claim 1, characterized in that the sensor (5) is covered completely or partially by a transmission medium transmitting the physical quantity.

5. The device as claimed in [one of claims 1 through 4] claim 1, characterized in that the biocompatible material with which the device is covered forms the transmission medium.

6. The device as claimed in [one of claims 1 through 5] claim 1, characterized in that the coil windings (3) in the area of their connection to the electronic module (4) extend in a substantially rectilinear manner.

7. The device as claimed in [one of claims 1 through 6] claim 1, characterized in that the coil windings (3) extend substantially in the entire implant part lying outside the field of vision of the eye.

8. The device as claimed in [one of claims 1 through 7] claim 1, characterized in that the sensor (5) is designed as a pressure sensor.

10. The device as claimed in [one of claims 1 through 9] claim 1, characterized in that the sensor (5) lies outside the field of vision of the eye in an area which does not overlap the surface of the coil windings (3).

11. The device as claimed in [one of claims 1 through 10] claim 1, characterized in that the sensor (5) lies inside the ring formed by the coil (1).

12. The device as claimed in [one of claims 1 through 11] claim 1, characterized in that the implant (6) is designed as an intraocular lens, and in that the annular support (2) in the area of the optic lens part (8) has a cutout which lies inside the coil windings (3).

13. The device as claimed in [one of claims 1 through 12] claim 1, characterized in that oblong holes (9) are formed in the implant material between the coil (1) and the implant part lying in the field of vision, in particular the optic lens part (8) of the intraocular lens.

15. The device as claimed in [one of claims 1 through 14] claim 1, characterized in that the surface or surfaces in which the coil (1) is arranged extends or extend approximately perpendicular to the optic axis (10) of the implant (6) designed as an intraocular lens.

16. The device as claimed in [one of claims 1 through 15] claim 1, characterized in that the coil (1) is arranged on one surface and the electronic module (4) on the other surface of the annular support (2; 16).

17. The device as claimed in [one of claims 1 through 11 and 15, 16] claim 1, characterized by an annular implant body (16) made of at least partially flexible material which forms the support for the coil (1).

10/089363

JC13 Rec'd PCT/PTG 25 MAR 2002

[Patent application]

MESOTEC

Gesellschaft für medizinische

Sensortechnik mbH

Vahrenwalder Str. 7

D-30165 Hanover

Acritec Gesellschaft für

ophthalmologische Produkte mbH

Linderstr. 24

D-16548 Glienicke

[Title of the invention]

Device for measuring physical quantities,
especially for measuring pressure in the eye

3/p r t s

JC13 Rec'd PCT/PTG 25 MAR 2002

- 2 -

[Description]

The invention relates to a device according to the preamble of patent claim 1, as known from DE 197 28 069 C1.

[Prior art]

The known device is used for measuring the intraocular pressure and comprises a foldable implant on which, outside the field of vision of the eye, there is a telemetry system having a pressure sensor and a transmitter device with coil. With the transmitter device, information corresponding to the sensor signals can be fed wirelessly to a receiver device arranged outside the eye. The received information is converted into reproducible data in an evaluation device connected to the receiver device.

In the known device, the telemetry system which can be implanted in the eye can have a data logger in which the measurement data delivered continuously from the pressure sensor can be stored and from which the measurement data can, when necessary, be retrieved for a limited time in transmit-receive mode.

[Object of the invention]

The object of the invention is to make available a device of the type mentioned above which can be folded or rolled and has excellent receive and transmit quality.

According to the invention, this object is achieved by the characterizing features of patent claim 1, the subclaims defining advantageous developments of the invention.

)

In the invention, the coil is arranged flat on a foldable support, in particular a support film, in the form of a plurality of adjacent coil windings in one plane surface. The telemetry device containing the electronics and/or the sensor are preferably contained in at least one electronic module (chip) and likewise applied with electrical contact to the coil on the foldable support. This arrangement is embedded in a foldable biocompatible implant material, in particular of polyorganosiloxane, e.g. polydimethylsiloxane. Here, the implant material can be used not only as a covering for the transmitter device and telemetry device, but also as a transmission medium to the sensor for the physical quantity to be measured, which especially can be the intraocular pressure or the temperature in the eye. That is to say, in a preferred embodiment, the sensor is also surrounded by the biocompatible implant material. However, it is also possible to leave the sensor uncovered on a sensor surface, which is sensitive to the physical quantity to be measured or recorded, or in a defined sensor area. The physical quantity to be measured and present in the eye, for example the intraocular pressure or temperature, then acts directly on

the sensor surface or this sensor area. For the physical quantity, it is also possible to use a transmission medium other than the implant material.

By means of the planar configuration of the coil with a plurality of mutually adjacent coil windings which preferably lies in a plane perpendicular to the optic axis of the eye or of the implant designed as intraocular lens, a high transmit and receive quality is obtained without impairing the foldability or rollability of the implant material. Moreover, the necessary compatibility with the eye is achieved for the whole device. In addition to one planar layer, it is also possible for a plurality of planar layers (planes) lying one above the other to be provided for the coil windings.

In a preferred manner, the implant is designed, as an intraocular lens, the telemetry device and the transmitter device with the coil being accommodated outside the optic lens part, in particular mainly in the area of the haptic part of the intraocular lens surrounding the optic part of the lens. For this purpose, the haptic part can have an annular area which surrounds the optic lens part and within which the planar arrangement of the coil windings is accommodated. The coil windings are preferably designed as planar electrical conductor tracks which are preferably made of precious metal, especially gold. The conductor tracks of

the coil windings are produced on the support film using conventional planar technology, for example by metal deposition, in particular electrodeposition, as are known in microstructuring processes.

The implant can also be of annular design. The coil windings are then arranged on at least one of the ring surfaces. The annular implant is preferably fixed on the sulcus of the eye. The ring can be made partly of a hard material, in particular PMMA, and partly of a flexible material, in particular silicone. The implant is preferably covered with a biocompatible material, for example silicone rubber. The ring can also be made entirely of silicone, in which case a stabilizing haptic part made in particular of PMMA or of another rigid material is provided.

The support film is designed as a thin flexible and foldable film which ensures a good adhesion for the metal of the coil windings, and in particular the film material has dielectric properties and can be made of a suitable plastic, e.g. a polyimide.

On account of the high degree to which the device can be rolled or folded, it can be implanted in the eye without having to modify the usual techniques of minimally invasive surgery. In this way, microelectronic and sensoric components

can be fitted in the eye for wireless energy and signal transmission, for example in the form of an artificial intraocular lens which is foldable. The intraocular lens unfolds after implantation.

[Examples]

The invention is explained in more detail on the basis of an illustrative embodiment and with reference to the figures, in which:

Figure 1 shows a plan view of an illustrative embodiment designed as an intraocular lens;

Figure 2 shows a plan view of an embodiment of a telemetry system which can be used in the illustrative embodiment represented in Figure 1;

Figure 3 shows a sectional representation of the telemetry system represented in Figure 2;

Figure 4 shows a sectional representation of a telemetry system in a further illustrative embodiment;

Figure 5 shows an illustrative embodiment of an annular implant;

Figure 6 shows a further illustrative embodiment of an annular implant with closed haptic loops; and

Figure 7 shows an illustrative embodiment of an annular implant with open haptic loops.

The illustrative embodiment of an eye implant 6 shown is designed as an intraocular lens. The latter has an optic lens part 1 which can be fitted in the visual field of the eye. The optic lens part 8 has an optic axis 10 which is substantially perpendicular to the plane of the drawing in Figure 1. In the implanted state, the optic axis is oriented substantially on the visual axis of the eye. The optic lens part 8 substantially covers the visual field of the eye.

Situated on an annular support which is designed as a support film (Figure 2) and which is flexible, i.e. can be folded and rolled, there is a coil 1 which forms the inductance in the transmit-receive device. The coil is made up of planar coil windings 3 in the form of conductor tracks lying adjacent to one another. The conductor tracks of the coil windings 3 lie next to one another in a plane which is substantially perpendicular to the optic axis 10. The width of a coil winding is of the order of ca. 3 to 90 μm , preferably ca. 10 to 90 μm . About 10 to 65 coil windings can be provided in a particular plane for the coil 1. By means of such a design of

the coil 1, the ability of the support film 2 to be folded, rolled and, where appropriate, bent remains unimpaired. The coil windings 3 can be produced, for example, by electro-deposition, as is known in microstructuring processes. In the illustrative embodiment shown, the coil 1 is situated on a circular surface. However, to adapt it to the site of use of the implant 6, the coil can also be made oval or oval-like or can have another configuration.

The electronics of the telemetry system, accommodated in an electronic module (chip) 4, are also situated on the support film 2, it being possible of course to use a plurality of electronic modules. A sensor 5 for recording the physical quantity to be measured, in particular the intraocular pressure, can preferably be provided in an edge area on this electronic module 4. As Figure 3 shows, the electronic module 4 is suitably contacted with the coil 1 (electrical contacts 11). In the area of the electronic module 4, in order to make contacting easier, the coil windings 3 preferably extend in a substantially rectilinear manner, as is shown in a rectilinear area of windings 7 in Figure 2. The electrical contact 11 between the coil 1 and the electronic module 4 can be obtained in hybrid technology or flip-chip technology by bonding. The electrical contact points 11 (Figure 3) can be formed by gold bumps with a thickness of 30 μm and less. In addition to a monolithic structure, the chip or the

electronic modules can be incorporated in one or more films and are thus able to be folded and rolled.

The planar coil windings have a thickness (height) in the region of 5 to 60 μm . The height of the electronic module 4 is ca. 600 μm and can be substantially less than for example 300 μm . The surface of the electronic module 4 is ca. 2.0 mm x 2.0 mm. The thickness of the support film can be about 8 μm . The coil can have an external radius of ca. 5.15 mm and an internal radius of ca. 3.85 mm. The area of the support film 2 lying to the inside of the coil 1 can be punched out so that the support film 2 is present as an annular support film which is substantially covered with the coil windings 3.

The support film 2 with the telemetry devices arranged thereon, as shown in Figures 2 and 3, is covered completely, in particular by embedding, with a biocompatible implant material, in particular lens material. The implant material or lens material also covers the sensor 5 which is designed in particular as a pressure sensor. Figure 1 shows the intraocular lens into which the telemetry system shown in Figures 2 to 4 is embedded. The dimensions indicated in Figure 1 are illustrative and can be varied within the limits permitted for implantation in the eye.

As can be seen from Figure 1, the coil 1 is situated within an annular haptic area which concentrically surrounds the optic lens part 8. This can be a circular ring or an oval or oval-like ring. An annular area 12 of the lens material lying between this annular haptic area and the optic lens part 8 is provided with oblong holes 9 which, at their border edges, extend approximately concentrically about the optic axis 10 with respect to the annular coil 1 and the annular area 12. These oblong holes 9 not only facilitate the folding or rolling of the lens, but also aid the fixing of the lens in the eye since ocular tissue can grow into these oblong holes. As can also be seen from Figure 1, the sensor 5 is situated in proximity to the optic lens part 8. It lies between the optic lens part 8 and the inner edge of the coil 1 in an area which does not overlap the surface of the coil 1. The sensor 5 is enclosed by a lens material which is situated between two ends of the oblong holes 9 in the annular area 12 of the lens material. The lens material serves to transmit the physical quantity to be measured in the eye, for example the temperature or the intraocular pressure. A polyorgano-siloxane, in particular polydimethylsiloxane, is preferably used for the lens material. It is also possible to provide another transmission medium in the area of the sensor 5 or of a sensor area responding to the physical quantity (e.g. pressure, temperature) or to leave this area uncovered, as will be explained below with reference to Figure 4.

The external diameter of the intraocular lens can be about 12 mm or less, e.g. 8.5 mm. The diameter of the optic lens part 8 can be 6 mm or less, for example 4.8 mm. The thickness of the lens in the center of the optic lens part 8 can be about 0.780 mm or less. In the nonoptic area, the thickness can be 0.500 mm or less, but in the area of the electronic module 4 it must be ensured that this is completely enclosed by the lens material and, accordingly, the lens in this area has a corresponding thickness. The length of the oblong holes 9 can be about 4.6 mm or less. The width can be 1.2 mm or less.

In the illustrative embodiment shown in Figure 3, the coil 1 and the electronic module 4 are situated on the same side of the support film 2. In the illustrative embodiment shown in Figure 4, the coil 1 is situated on one side of the support film 2 and the electronic module 4 on the other side of the support film 2. The electrical contacting 11 between the coil 1 and the electronic module 4 is effected with the aid of contacts through the support film 2.

As can be seen from the illustrative embodiment in Figure 4, an area of the sensor 5 sensitive to the physical quantity to be measured can be left uncovered. In the illustrative embodiment shown, this is a sensor surface 13. For this

- 12 -

purpose, a cutout can be provided in the support film 2. This cutout is also situated in the covering implant or intraocular lens material. However, it is also possible to use, in the cutout, a material transmitting the physical quantity which is different than the implant material. In the illustrative embodiment shown in Figure 4, the exposed sensor surface 13 is situated on the inside of the sensor 5. The exposed sensor surface can also lie on the other side, i.e. on the outside of the sensor 5.

As can be seen from Figure 1, the implant or lens material can be folded or rolled about fold edges 14 which extend approximately parallel to one another and lie on both sides of the electronic module 4. Even if the electronic module 4 is made of a nonfoldable monolithic module, it is still possible to obtain a considerable reduction in the implant cross section for implantation. The two fold edges 14 extend on both sides of the electronic module. The implant can also be folded along a fold edge 15 which extends through the lens center (optic axis 10). It will be apparent from this that the implant has a large number of folding possibilities, even when the electronic module 4 is of monolithic design. By means of the special design of the coil 1, the latter can be folded while obtaining a high inductance.

A memory can be provided in the electronic module 4, which memory stores the pressure values continuously recorded by the sensor, in particular the pressure sensor 5. These pressure values can be retrieved from this memory from time to time, for example at weekly intervals, and transmitted from the telemetry device to a receiver device (not detailed) with attached evaluation device, as is described for example in German patent specification DE 197 28 069 C1. It is also possible for the electronic module 4 to be formed from foldable support material, so that a deformation of the intraocular lens to a small diameter is possible and only a small incision needs to be made in the eye for the implantation. The lens material is designed in such a way that it unfolds after implantation and adopts the desired lens shape.

In the illustrative embodiments shown in Figures 5 to 7, an implant body 16 is designed in an annular shape. The cutout provided in the inside of the ring is dimensioned at least so that it lies outside the field of vision when the annular implant is arranged in the eye. The coil (not shown) is designed in the manner shown in Figure 2. It is situated on one or both surfaces of the annular implant. The attachment of the sensor 5 and of the electronic module 4 is effected in the same way as has been explained in the previous illustrative embodiments. The sensor 5 is situated inside the

In the illustrative embodiment shown in Figure 6, the annular implant body 16 has closed haptic loops 19. The illustrative embodiment shown in Figure 7 has open haptic loops 20. The annular implant bodies 16 of illustrative embodiments 6 and 7 are preferably made of silicone rubber. The haptic loops 19 and 20 are preferably made of a rigid material, in particular PMMA. In the illustrative embodiment shown in Figure 7, fixation holes 21 are provided in the open haptic loops 20. This ensures a stable positioning of the implant body 16 in the eye. The illustrative embodiments in Figures 5 to 7 are suitable for fixation in the sulcus of the eye. If appropriate, additional fixation holes (not shown) can also be provided in the illustrative embodiment in Figure 5.

The illustrative embodiments in Figures 5, 6 and 7 can be completely covered with an envelope of silicone rubber or with another biocompatible envelope. The intraocular pressure is transmitted to the sensor surface of the pressure sensor 5 via this resilient envelope. The envelope material forms the transmission medium for transmitting the intraocular pressure to the sensor surface of the sensor 5.

Thus, in all of the illustrative embodiments, it is possible to achieve a complete covering of the implant with biocompatible material and a perfect transmission of pressure to the sensor surface of the sensor 5 via the envelope material.

[List of reference numbers]

- 1 coil
- 2 support film
- 3 coil windings
- 4 electronic module (chip)
- 5 sensor, in particular pressure sensor
- 6 implant, in particular intraocular lens
- 7 rectilinear area of windings
- 8 optic lens part
- 9 oblong hole
- 10 optic axis
- 11 electrical contact
- 12 annular area
- 13 sensor surface
- 14 fold edge
- 15 fold edge
- 16 annular implant body
- 17 rigid ring part
- 18 flexible ring part
- 19 closed haptic loop
- 20 open haptic loop
- 21 fixation hole

[Patent Claims]

1. A device for measuring physical quantities in the eye, with a foldable implant on which, arranged outside an implant part covering the field of vision of the eye, there is a telemetry device having a sensor and having a transmitter device with coil for wireless transmission of information corresponding to the sensor signals, and with a receiver device which is arranged outside the eye and receives the information sent by the transmitter device, and with an evaluation device which converts the received information into reproducible data, characterized in that, on an annular foldable support (2; 16), the coil (1) is arranged in the form of a plurality of adjacent coil windings in at least one surface, and at least one electronic module (4) containing the electronics of the telemetry device is electrically contacted with the coil, and in that this arrangement is embedded in the foldable biocompatible implant material.
2. The device as claimed in claim 1, characterized in that coil windings (3) are formed from planar electrical conductor tracks.

3. The device as claimed in claim 1 or 2, characterized in that the coil windings (3) are arranged in one or more planes.
4. The device as claimed in one of claims 1 through 3, characterized in that the sensor (5) is covered completely or partially by a transmission medium transmitting the physical quantity.
5. The device as claimed in one of claims 1 through 4, characterized in that the biocompatible material with which the device is covered forms the transmission medium.
6. The device as claimed in one of claims 1 through 5, characterized in that the coil windings (3) in the area of their connection to the electronic module (4) extend in a substantially rectilinear manner.
7. The device as claimed in one of claims 1 through 6, characterized in that the coil windings (3) extend substantially in the entire implant part lying outside the field of vision of the eye.

8. The device as claimed in one of claims 1 through 7, characterized in that the sensor (5) is designed as a pressure sensor.
9. The device as claimed in claim 8, characterized in that the pressure sensor (5) continuously measures the intraocular pressure, and the electronics of the telemetry device have a memory in which the sensor signals are stored for a temporally limited transmission to a receiver device.
10. The device as claimed in one of claims 1 through 9, characterized in that the sensor (5) lies outside the field of vision of the eye in an area which does not overlap the surface of the coil windings (3).
11. The device as claimed in one of claims 1 through 10, characterized in that the sensor (5) lies inside the ring formed by the coil (1).
12. The device as claimed in one of claims 1 through 11, characterized in that the implant (6) is designed as an intraocular lens, and in that the annular support (2) in the area of the optic lens part (8) has a cutout which lies inside the coil windings (3).

13. The device as claimed in one of claims 1 through 12, characterized in that oblong holes (9) are formed in the implant material between the coil (1) and the implant part lying in the field of vision, in particular the optic lens part (8) of the intraocular lens.
14. The device as claimed in claim 13, characterized in that the sensor (5) lies in an annular area (12) of the implant material in which the oblong holes (9) extend.
15. The device as claimed in one of claims 1 through 14, characterized in that the surface or surfaces in which the coil (1) is arranged extends or extend approximately perpendicular to the optic axis (10) of the implant (6) designed as an intraocular lens.
16. The device as claimed in one of claims 1 through 15, characterized in that the coil (1) is arranged on one surface and the electronic module (4) on the other surface of the annular support (2; 16).
17. The device as claimed in one of claims 1 through 11 and 15, 16, characterized by an annular implant body (16) made of at least partially flexible material which forms the support for the coil (1).

18. The device as claimed in claim 17, characterized in that the annular implant body (16) can be fixed in the sulcus of the eye.

$\rho = \frac{2\pi \times 10^{-10} \text{ cm}}{1.25 \times 10^{-10} \text{ cm}} = 1.6 \times 10^{-10} \text{ cm}$



(10) Internationale Veröffentlichungsnummer
WO 01/21063 A1

(71) Anmelder (für alle Bestimmungsstaaten mit Ausnahme von US): ACRITEC GESELLSCHAFT FÜR OPHTHALMOLOGISCHE PRODUKTE MBH [DE/DE]; Lindenstrasse 24, 16548 Glienicke (DE). MESOTEC GESELLSCHAFT FÜR MEDIZINISCHE SENSORTECHNIK MBH [DE/DE]; Vahrenwalder Strasse 7, 30165 Hannover (DE).

(72) Erfinder; und
(75) Erfinder/Anmelder (nur für US): KREINER, Christine [DE/DE]; Harthäuser Strasse 30a, 81545 München (DE). BÖDECKER, Volker [DE/DE]; Vahrenwalder Strasse 7, 30165 Hannover (DE). SCHNAKENBERG, Uwe [DE/DE]; Kullenhofwinkel 36, 52074 Aachen (DE). ULLERICH, Stella, Marianne [DE/DE]; Adalbertsteinweg

[Fortsetzung auf der nächsten Seite]

(72) Erfinder; und
(75) Erfinder/Anmelder (nur für US): KREINER, Christine [DE/DE]; Harthäuser Strasse 30a, 81545 München (DE). BÖDECKER, Volker [DE/DE]; Vahrenwalder Strasse 7, 30165 Hannover (DE). SCHNAKENBERG, Uwe [DE/DE]; Kullenhofwinkel 36, 52074 Aachen (DE). ULLERICH, Stella, Marianne [DE/DE]; Adalbertsteinweg


(72) Erfinder; und
(75) Erfinder/Anmelder (nur für US): KREINER, Christine [DE/DE]; Harthäuser Strasse 30a, 81545 München (DE). BÖDECKER, Volker [DE/DE]; Vahrenwalder Strasse 7, 30165 Hannover (DE). SCHNAKENBERG, Uwe [DE/DE]; Kullenhofwinkel 36, 52074 Aachen (DE). ULLERICH, Stella, Marianne [DE/DE]; Adalbertsteinweg

(72) Erfinder; und
(75) Erfinder/Anmelder (nur für US): KREINER, Christine [DE/DE]; Harthäuser Strasse 30a, 81545 München (DE). BÖDECKER, Volker [DE/DE]; Vahrenwalder Strasse 7, 30165 Hannover (DE). SCHNAKENBERG, Uwe [DE/DE]; Kullenhofwinkel 36, 52074 Aachen (DE). ULLERICH, Stella, Marianne [DE/DE]; Adalbertsteinweg

(54) Bezeichnung: VORRICHTUNG ZUM MESSEN VON PHYSIKALISCHEN GRÖSSEN, INSBESONDERE ZUR DRUCKMESSUNG IM AUGE


(57) Abstract: The invention relates to a device for measuring physical quantities in the eye, especially for measuring the intraocular pressure. The inventive device comprises a foldable telemetry system containing a coil (1) which is flatly arranged on a foldable support. Said coil is completely embedded in the biocompatible implant material together with an electronic module (4) that contains the electronics of the telemetry system.

(57) Zusammenfassung: Eine Vorrichtung zum Messen von physikalischen Grössen im Auge, insbesondere des Augeninnendrucks mit einem faltbaren Telemetriesystem, enthaltend eine auf einem faltbaren Träger, flächig angeordnete Spule (1), welche zusammen mit einem die Elektronik des Telemetriesystems enthaltenden elektronischen Baustein (4), vollständig im biokompatiblen Implantatmaterial eingegossen ist.



WO 01/21063 A1

Fig. 1



10/089363

Fig. 2




Fig. 3








Fig. 4





#4

UNITED STATES OF AMERICA COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION		OFGS FILE NO P/4074-8																																														
<p>As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named) of the subject matter which is claimed and for which a patent is sought on the invention entitled</p> <p>DEVICE FOR MEASURING PHYSICAL QUANTITIES, ESPECIALLY FOR MEASURING PRESSURE IN THE EYE</p> <p>the specification of which is attached hereto, unless the following box is checked</p> <p><input checked="" type="checkbox"/> was filed on <u>22 September 2000</u> as United States patent Application Number or PCT International patent application number <u>PCT/EP00/09301</u> and was amended on _____ (if any)</p> <p>I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above</p> <p>I acknowledge the duty to disclose all information known to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.</p> <p>I hereby claim priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate or United States provisional application(s) listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed</p> <p>Prior Foreign or Provisional Application(s)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 25%;">COUNTRY</th> <th style="width: 30%;">APPLICATION NUMBER</th> <th style="width: 25%;">DATE OF FILING (day, month, year)</th> <th style="width: 20%;">PRIORITY CLAIMED UNDER 35 U.S.C. 119</th> </tr> <tr> <td>Germany</td> <td>199 45 879.0</td> <td>24 September 1999</td> <td>YES <u>X</u> NO ____</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td>YES ____ NO ____</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td>YES ____ NO ____</td> </tr> </table> <p>I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%;">UNITED STATES APPLICATION NUMBER</th> <th style="width: 35%;">DATE OF FILING (day, month, year)</th> <th style="width: 35%;">STATUS (patented, pending, abandoned)</th> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> <p>I hereby appoint customer no. 2352 OSTROLENK, FABER, GERB & SOFFEN, LLP, and the members of the firm, Samuel H. Weiner - Reg. No. 18,510; Jerome M. Berliner - Reg. No. 18,653; Robert C. Faber - Reg. No. 24,322; Max Moskowitz - Reg. No. 30,576; James A. Finder - Reg. No. 30,173; William O. Gray, III - Reg. No. 30,944; Louis C. Dujmich - Reg. No. 30,625; and Douglas A. Miro - Reg. No. 31,643, as attorneys with full power of substitution and revocation to prosecute this application, to transact all business in the Patent & Trademark Office connected therewith and to receive all correspondence</p> <p>SEND CORRESPONDENCE TO OSTROLENK, FABER, GERB & SOFFEN, LLP DIRECT TELEPHONE CALLS TO. 1180 AVENUE OF THE AMERICAS- NEW YORK, NEW YORK 10036-8403 (212) 382-0700 CUSTOMER NO. 2352</p> <p>I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">1-00 FULL NAME OF SOLE OR FIRST INVENTOR <u>Christine KREINER</u></td> <td style="width: 30%;">INVENTOR'S SIGNATURE <u>[Signature]</u></td> <td style="width: 30%;">DATE <u>7th June 2002</u></td> </tr> <tr> <td>RESIDENCE (City and either State or Foreign Country) <u>81545 München, Germany</u></td> <td colspan="2">COUNTRY OF CITIZENSHIP <u>Germany</u></td> </tr> <tr> <td colspan="3">POST OFFICE ADDRESS <u>Harthausen Strasse 30a, 81545 München, Germany</u></td> </tr> <tr> <td>2-00 FULL NAME OF SECOND JOINT INVENTOR (IF ANY) <u>Volker BODECKER</u></td> <td>INVENTOR'S SIGNATURE <u>[Signature]</u></td> <td>DATE <u>7. May 2002</u></td> </tr> <tr> <td>RESIDENCE (City and either State or Foreign Country) <u>30165 Hannover, Germany</u></td> <td colspan="2">COUNTRY OF CITIZENSHIP <u>Germany</u></td> </tr> <tr> <td colspan="3">POST OFFICE ADDRESS <u>Vahrenwalder Strasse 7, 30165 Hannover, Germany</u></td> </tr> </table>			COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119	Germany	199 45 879.0	24 September 1999	YES <u>X</u> NO ____				YES ____ NO ____				YES ____ NO ____	UNITED STATES APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)										1-00 FULL NAME OF SOLE OR FIRST INVENTOR <u>Christine KREINER</u>	INVENTOR'S SIGNATURE <u>[Signature]</u>	DATE <u>7th June 2002</u>	RESIDENCE (City and either State or Foreign Country) <u>81545 München, Germany</u>	COUNTRY OF CITIZENSHIP <u>Germany</u>		POST OFFICE ADDRESS <u>Harthausen Strasse 30a, 81545 München, Germany</u>			2-00 FULL NAME OF SECOND JOINT INVENTOR (IF ANY) <u>Volker BODECKER</u>	INVENTOR'S SIGNATURE <u>[Signature]</u>	DATE <u>7. May 2002</u>	RESIDENCE (City and either State or Foreign Country) <u>30165 Hannover, Germany</u>	COUNTRY OF CITIZENSHIP <u>Germany</u>		POST OFFICE ADDRESS <u>Vahrenwalder Strasse 7, 30165 Hannover, Germany</u>		
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119																																													
Germany	199 45 879.0	24 September 1999	YES <u>X</u> NO ____																																													
			YES ____ NO ____																																													
			YES ____ NO ____																																													
UNITED STATES APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)																																														
1-00 FULL NAME OF SOLE OR FIRST INVENTOR <u>Christine KREINER</u>	INVENTOR'S SIGNATURE <u>[Signature]</u>	DATE <u>7th June 2002</u>																																														
RESIDENCE (City and either State or Foreign Country) <u>81545 München, Germany</u>	COUNTRY OF CITIZENSHIP <u>Germany</u>																																															
POST OFFICE ADDRESS <u>Harthausen Strasse 30a, 81545 München, Germany</u>																																																
2-00 FULL NAME OF SECOND JOINT INVENTOR (IF ANY) <u>Volker BODECKER</u>	INVENTOR'S SIGNATURE <u>[Signature]</u>	DATE <u>7. May 2002</u>																																														
RESIDENCE (City and either State or Foreign Country) <u>30165 Hannover, Germany</u>	COUNTRY OF CITIZENSHIP <u>Germany</u>																																															
POST OFFICE ADDRESS <u>Vahrenwalder Strasse 7, 30165 Hannover, Germany</u>																																																

☒ CONTINUED ON PAGE 2

